

Flexi Button




Multi-purpose, hard-wearing matting in a stylish button pattern.



Practical and stylish in equal measures, Flexi Button is the perfect floor covering for commercial and light industrial workplaces.

The deep stud design not only looks good, it's also extremely hard-wearing and easy to clean. The raised elevation means it can withstand light spillages, making it ideal for workplaces where liquids are present and employees need protection underfoot.



Features:



Deep stud design



Hard-wearing vinyl sheets



Made from flexible PVC



Supplied in a convenient roll format



Benefits:



Good slip resistance



Resistant to chemicals, acids and oils



Easy to cut to fit on site; contours to subfloor



Quick to install



Plastic Extruders Ltd.

Russell Gardens, Wickford
Essex, SS11 8DN
+44 (0) 1268 571 116

UK + USA manufactured matting products:
plastexmatting.com



Flexi Button

Data sheet



Standard sizes:

| | |
|----------------------|---------------------------------------|
| Product | Flexi Button |
| Height | 3.3mm (1/8") |
| Standard roll option | 20 x 0.98m (65'7" x 3'2") |
| Weight | 4.29kg/m ² (0.88 lb/sq.ft) |

Tolerances:

| | Height (+/- 0.5mm) | Lengths (0+0.3 m) | Widths (+/- 1cm) |
|--------------|--------------------|-------------------|------------------|
| Flexi Button | 3.3 mm | 20 m | 98 cm |

All dimensions are nominal

Technical information:

| | |
|-------------|--|
| Chemical | Resistant to most acids, alkalines and oils. You can read more about specific chemical resistances by downloading this information sheet . |
| Composition | Flexible Polyvinyl Chloride (PVC) |
| Environment | Flexi Button is 100% recyclable and contains no substances included in the SVHC list under REACH. |
| Fire | EN 13501-1: 2007-Bfl-S1 |
| Reversion | Thermoplastic shrinkage can result in size reductions up to 2%. This may be accelerated in hot environments. You can read more about the causes of shrinkage by downloading this information sheet . |
| Thermal | Designed to function at temperatures from -23°C and up to +60°C. Slight size variation may occur at temperature extremes. |
| UV light | Resistant to PVC degradation |
| Warranty | Two years. Visit our policies page for more information about warranties |

Installation:

Flexi Button's one-piece construction means installation is simple:

- Supplied in convenient roll formats
- Easy to cut to size
- Contours to the sub floor

Cleaning:

Keeping Flexi Button looking good is easy:

- Easy to clean with a vacuum or mop
- No special cleaning tools needed

Colours:



Dark grey



Blue



Black

More colours
available
upon request